


**4 Channel Line Output Module  
DATASHEET**



The QUAD-OUT is a 4 channel modular output card for use with Ivie MAP series devices. Each Quad-Out provides 4 channels of balanced line audio output with software controllable gain, level, mute, and signal inversion.

**BENEFITS**

- Modular compatibility with any iFlex MAP mixer product
- Fully software programmable/controllable
- 1U Rack footprint

**FEATURES**

Frequency response(20 Hz - 20 KHz)	+0/- 0.25dB	Sampling Rate	48 KHz
THD+N (20 Hz - 20KHz )	.01%@10dBV Output	D/A Convertors (bit rate)	24-bit
Equivalent Input Noise (20 Hz - 20 KHz)	< -125dBu	Compliances	EU Directive 2006/95/EC EU Directive 2004/108/EC RoHS Directive 2002/95/EC
Dynamic Range (20Hz - 20KHz, 0dB)	> 108dB		
Crosstalk	< -75dB		
Output Impedance	200 Ohms		
Maximum Output	+24dBu		

**ARCHITECTS & ENGINEERS SPECIFICATION**

The line output shall be a 4-channel card designed exclusively for use with iFlex MAP devices. The modular card shall provide 4 balanced outputs on euro-block connections. Software configuration and control for each output shall include:mute, level, and signal inversion. Digital to Analog conversion shall be 24-bit with a sampling rate of 48kHz. Performance specifications (20Hz-20kHz) shall be: Frequency Response +0/-0.25dB; THD+N <0.01% +24V dBu Output; and Dynamic Range >108dB. The modular output card shall be compliant with EU Directive 2006/95/EC, EU Directive 2004/108/EC, and EU Directive 2002/95/EC, the RoHS Directive. Warranty shall be 5 years. The output card shall be QUAD-OUT.